BESVIEW

Shenzhen Besview Security Limited



Product Catalogue

2025

BESVIEW

Shenzhen Besview Security Limited

Professional ***OEM*** / ***ODM*** CCTV Camera Manufacturer

Besview Security Limited

www.besview.com

5th Floor#A Building, Yajiashi Industrial Park, Huating Rd, Dalang, Shenzhen, China, P.R.C. 518109

+86-0755-33282388 +86-15986680410 sales@besview.com

Besview Product Catalogue

IPC Active Deterrence Camera Series(Red&Blue Light)---- 01
IPC Super ColorVu Camera Series(1/1.8" Sensor+F1.0 Lens)---- 02
IPC PTZ Camera Series---- 03
IPC Dual Light ColorVu Camera Series(F1.6/F1.0 Lens)---- 04
IPC IR Night Vision Camera Series---- 05
IPC 180 Degree Super Wide Angle Series---- 06
IPC LPR IP Camera Series---- 07
IPC Mini Hidden&Fisheye Camera Series---- 08
HD Analog Camera Series---- 09
Smart Home Series(Wifi Camera)---- 10
4G Camera / 4G Solar Camera Series---- 11
USB Camera Series ---- 12
AI Camera Systems---- 13
IPC USB HDMI Camera PCBA Customized Series---- 14
A Series NVR ---- 15
U Series NVR---- 16
CCTV NVR System Series---- 17
DVR Series---- 18
CCTV DVR System Series---- 19
Camera Accessories---- 20

Company Profile



Shenzhen Besview Security Limited is one of the leading manufacturers in surveillance industry in China with more than 25 years experience. We have more than 50 engineers &technical support, 100 workers, 3000m² production area. Our products include IP Cameras, WiFi Cameras, HD Analog cameras, Video Conference Cameras, Streaming Cameras, NVRs, XVRs,etc.

Customers' needs are the directions of our efforts. Since our foundation, Besview has endeavored to provide more competitive products and solutions to all our customers. OEM and ODM services are Besview's biggest advantage, we can provide LOGO printing, Color Box Design, Housing Design, PCB board Design and Software Customization Services (Web Logo/Software Functions, Protocols) etc. CGI, API and SDK of our IP cameras also can be provided to enhance our customers' competitiveness.

Our products have been sold to more than 100 countries around the world, and have received a lot of praise and endorsements from customers. Looking forward to your inquiry and working with you.

Your Security, our Responsibility!

ISC West 2018



APS 2019



ISC West 2019





Authoritative Certificate



CPSE 2023



ISC West2023



ISC West2024




Company style











IPC Active Deterrence Camera Series(Red&Blue Light)

Professional OEM/ODM CCTV Camera Manufacturer.



- BC-IE40BBW-5MS(5MP@25fps)
- BC-IE40BBW-6M6(6MP@25fps)
- BC-IE40BBW-8ME(8MP@20fps)
- 5X 2.7-13.5mm Motor Lens
- Two Way Audio/SD Card
- IR: 25m + White Light :15m
- IP66,PoE&DC12V



- BC-IE35BBW-5MS(5MP@25fps)
- BC-IE35BBW-6M6(6MP@25fps)
- BC-IE35BBW-8ME(8MP@20fps)
- 5X 2.7-13.5mm Motor Lens
- Two Way Audio/SD Card
- IR: 25m + White Light :15m
- IP66,PoE&DC12V



- BC-IE252BW-5MS(5MP@25fps)
- BC-IE252BW-6M6(6MP@25fps)
- BC-IE252BW-8MS(8MP@20fps)
- BC-IE252BW-8MH(8MP@30fps)
- 2.8mm F1.0 Fixed Lens
- Two Way Audio/SD Card
- IR: 20m + White Light :15m
- IP66,PoE&DC12V



- BC-IB78BBW-5MS(5MP@25fps)
- BC-IB78BBW-6M6(6MP@25fps)
- BC-IB78BBW-8MS(8MP@20fps)
- BC-IB78BBW-8MH(8MP@30fps)
- 5X 2.7-13.5mm Motor Lens
- Two Way Audio/SD Card
- IR: 30m + White Light :20m
- IP66,PoE&DC12V



- BC-IB682BW-5MS(5MP@25fps)
- BC-IB682BW-6M6(6MP@25fps)
- BC-IB682BW-8MS(8MP@20fps)
- BC-IB682BW-8MH(8MP@30fps)
- 2.8mm F1.0 Fixed Lens
- Two Way Audio/SD Card
- IR: 20m + White Light :15m
- IP66,PoE&DC12V



Features

1. 8MP(4K)/6MP/5MP H.265 PoE IP Camera
2. Fixed Lens/ Motorized Lens Optional
3. Support 2DNR/ 3DNR/ Sense-up/ WDR Functions etc.
4. Built-in Mic./Speaker or Audio in/out Optional(RCA Cable Interface)
5. Support RTSP&Onvif(17.2 with profile S),Compatible with HIK/DH/UNV/TVT NVRS
6. SDK/CGI Available

(NDAA Compliant)

IPC Super ColorVu Camera Series(1/1.8" Sensor)

Professional OEM/ODM CCTV Camera Manufacturer.



- BC-IE402WW-5MA(5MP@25fps)
- BC-IE40BWW-5MA(5MP@25fps)
- BC-IE402WW-8MA(8MP@20fps)
- BC-IE40BWW-8MA(8MP@20fps)
- 1/1.8" Sensor
- 2.8mm F1.0 M16 Fixed Lens
- 5X 2.7-13.5mm Motor Lens
- Two Way Audio
- White Light :20m
- IP66,PoE,DC12V



- BC-IE352WW-5MA(5MP@25fps)
- BC-IE35BWW-5MA(5MP@25fps)
- BC-IE352WW-8MA(8MP@20fps)
- 1/1.8" Sensor
- 2.8mm F1.0 M16 Fixed Lens
- 5X 2.7-13.5mm Motor Lens
- Two Way Audio
- White Light :20m
- IP66,PoE,DC12V



- BC-IE252WW-5MA(5MP@25fps)
- BC-IE252WW-8MA(8MP@20fps)
- 1/1.8" Sensor
- 2.8mm F1.0 M16 Fixed Lens
- Two Way Audio
- White Light :20m
- IP66,PoE,DC12V



- BC-IE2A2WW-5MA(5MP@25fps)
- BC-IE2A2WW-8MA(8MP@20fps)
- 1/1.8" Sensor
- 2.8mm F1.0 M16 Fixed Lens
- Two Way Audio
- White Light :20m
- IP66,PoE,DC12V



- BC-IV302WW-5MA(5MP@25fps)
- BC-IV30BWW-5MA(5MP@25fps)
- BC-IV302WW-8MA(8MP@20fps)
- BC-IV30BWW-8MA(8MP@20fps)
- 1/1.8" Sensor
- 5X 2.7-13.5mm Motor Lens
- White Light :20m
- IP66,PoE,DC12V



- BC-IV222WW-5MA(5MP@25fps)
- BC-IV222WW-8MA(8MP@20fps)
- 1/1.8" Sensor
- 2.8mm F1.0 M16 Fixed Lens
- Two Way Audio
- White Light :20m
- IP66,PoE,DC12V



- BC-IB782WW-5MA(5MP@25fps)
- BC-IB78BWW-5MA(5MP@25fps)
- BC-IB782WW-8MA(8MP@20fps)
- BC-IB78BWW-8MA(8MP@20fps)
- 1/1.8" Sensor
- 2.8mm F1.0 M16 Fixed Lens
- 5X 2.7-13.5mm Motor Lens
- Two Way Audio
- White Light :20m
- IP66,PoE,DC12V



- BC-IB682WW-5MA(5MP@25fps)
- BC-IB682WW-8MA(8MP@20fps)
- 1/1.8" Sensor
- 2.8mm F1.0 M16 Fixed Lens
- Two Way Audio
- White Light :20m
- IP66,PoE,DC12V

Features

1.8MP/5MP H.265 PoE IP Camera

2.Support 2DNR/ 3DNR/ Sense-up/ WDR Functions etc.

3.Built-in Mic./Speaker or Audio in/out Optional(RCA Cable Interface)

4.Support RTSP&Onvif(17.2 with profile S),Compatible with HIK/DH/UNV/TVT NVRS

5.SDK/CGI Available

(NDAA Compliant)

IPC PTZ Camera Series

Professional OEM/ODM CCTV Camera Manufacturer.



- BC-IP202RW-2MS(2MP@30fps)
- BC-IP202RW-5MH(5MP@30fps)
- BC-IP202RW-8MS(8MP@20fps)
- BC-IP202RW-8MH(8MP@30fps)
- 2.8mm F1.6 Fixed Lens
  (Digital Zoom Optional)
- Pan:0~355° /Tilt:0~90°
- IR range:30-35m
- IP66,PoE&DC12V



- BC-IP30BRW-2MS(2MP@30fps)
- BC-IP30BRW-5MH(5MP@30fps)
- BC-IP30BRW-8MS(8MP@20fps)
- BC-IP30BRW-8MH(8MP@30fps)
- 5X 2.7-13.5mm Motor Lens
  5~60mm 12X (Optional)
- Pan:0~355° /Tilt:0~90°
- IR range:30-35m
- IP66,PoE&DC12V



- BC-IP32BRW-5MS(5MP@25fps)
- BC-IP32BRW-6M6(6MP@25fps)
- BC-IP32BRW-8MS(8MP@20fps)
- BC-IP32BRW-8MH(8MP@30fps)
- 5X 2.7-13.5mm Motor Lens
  (5X Optical*3X Digital=15X)
- Pan:0~350° /Tilt:0~90°
- IR range:30-35m
- IP66,PoE&DC12V



- BC-IP29BRW-5MS(5MP@25fps)
- BC-IP29BRW-6M6(6MP@25fps)
- BC-IP29BRW-8MS(8MP@20fps)
- BC-IP29BRW-8MH(8MP@30fps)
- 5X 2.7-13.5mm Motor Lens
  (5X Optical*3X Digital=15X)
- Pan:0~350° /Tilt:0~90°
- IR range:30-35m
- IP66,PoE&DC12V

AI ONVIF ABSOLUTE MOVE SPEED CAMERA 200X ZOOM PTZ




- BC-IP53YRW-5MS(5MP@25fps)
- BC-IP53YRW-8MS(8MP@20fps)
- BC-IP53YRW-8MH(8MP@30fps)
- 20X Optical (4.7-125mm Motor Lens)
  (20X Optical*10X Digital=200X)
- Pan:0~360°@45°/s
  Tilt:0~90°@45°/s
- IR Range:100-120m
- Plug&Play onvif compatibity
- IP66,PoE&DC12V

AI ONVIF ABSOLUTE MOVE SPEED CAMERA 300X ZOOM PTZ



- BC-IP60ZRW-5MS(5MP@25fps)
- BC-IP60ZRW-8MS(8MP@20fps)
- BC-IP60ZRW-8MH(8MP@30fps)
- 30X Optical (5-150mm Motor Lens)
  (30X Optical*10X Digital=300X)
- Pan:0~360°@45°/s
  Tilt:0~90°@45°/s
- IR Range:180-200m
- Plug&Play onvif compatibity
- IP66,PoE&DC12V



Features

1. 8MP(4K)/6MP/5MP/4MP/2MP H.265 PoE IP Camera
2. Fixed Lens/Motorized Lens Optional
3. Support 2DNR/ 3DNR/ Sense-up/ WDR Functions etc.
4. Built-in Mic./Speaker or Audio in/out Optional
   (RCA Cable Interface)
5. Support RTSP&Onvif(17.2 with profile S)&HIK Protocol
   Compatible with HIK/DH/UNV/TVT NVRS
6. SDK/CGI Available

(NDAA Compliant)

IPC Dual Light ColorVu Camera Series(F1.6/F1.0 Lens)

Professional OEM/ODM CCTV Camera Manufacturer.



- BC-IE252DW-4MP(4MP@25fps)
- BC-IE252DW-5MS(5MP@25fps)
- BC-IE252DW-6M6(6MP@25fps)
- BC-IE252DW-8MS(8MP@20fps)
- BC-IE252DW-8MH(8MP@30fps)
- 2.8mm Fixed Lens
- Two Way Audio
- Support SD Card, Max up to 256G
- IR: 20m + White Light :15m
- IP66,PoE,DC12V



- BC-IE352DW-5MS(5MP@25fps)
- BC-IE352DW-6M6(6MP@25fps)
- BC-IE352DW-8MS(8MP@20fps)
- BC-IE352DW-8MH(8MP@30fps)
- 2.8mm Fixed Lens
- Two Way Audio
- Support SD Card, Max up to 256G
- IR: 25m + White Light :15m
- IP66,PoE,DC12V



- BC-IE402DW-5MS(5MP@25fps)
- BC-IE402DW-6M6(6MP@25fps)
- BC-IE402DW-8MS(8MP@20fps)
- BC-IE402DW-8MH(8MP@30fps)
- 5X 2.7-13.5mm Motor Lens
- Two Way Audio
- Support SD Card, Max up to 256G
- IR: 25m + White Light :15m
- IP66,PoE,DC12V



- BC-IV222DW-2MS(2MP@30fps)
- BC-IV222DW-5MH(5MP@30fps)
- BC-IV222DW-8MS(8MP@20fps)
- BC-IV222DW-8MH(8MP@30fps)
- 2.8mm F1.6 Fixed Lens (Digital Zoom Optional)
- Two Way Audio
- Pan:0~355° /Tilt:0~90°
- IR range:30-35m
- IP66,PoE&DC12V



- BC-IV302DW-2MS(2MP@30fps)
- BC-IV302DW-5MS(5MP@25fps)
- BC-IV302DW-6M6(6MP@25fps)
- BC-IV302DW-8MS(8MP@20fps)
- BC-IV302DW-8MH(8MP@30fps)
- 18pcs LEDs 25m IR Distance
- Two Way Audio
- 2.8mm Fixed Lens
- IP66,PoE&DC12V



- BC-IB682DW-4MP(4MP@25fps)
- BC-IB682DW-5MS(5MP@25fps)
- BC-IB682DW-6M6(6MP@25fps)
- BC-IB682DW-8MS(8MP@20fps)
- BC-IB682DW-8MH(8MP@30fps)
- 2.8mm Fixed Lens
- Two Way Audio
- Support SD Card, Max up to 256G
- IR: 20m + White Light :15m
- IP66,PoE,DC12V



- BC-IB782DW-5MS(5MP@25fps)
- BC-IB782DW-6M6(6MP@25fps)
- BC-IB782DW-8MS(8MP@20fps)
- BC-IB782DW-8MH(8MP@30fps)
- 2.8mm Fixed Lens
- Two Way Audio
- Support SD Card, Max up to 256G
- IR: 30m + White Light :20m
- IP66,PoE,DC12V



- BC-IB98BDW-5MS(5MP@25fps)
- BC-IB98BDW-6M6(6MP@25fps)
- BC-IB98BDW-8MS(8MP@20fps)
- BC-IB98BDW-8MH(8MP@30fps)
- BC-IB98BDW-9MS(12MP@20fps)
- 5X 2.7-13.5mm Motor Lens
- Two Way Audio
- Support SD Card, Max up to 256G
- IR: 30m + White Light :20m
- IP66,PoE,DC12V

Features

(NDAA Compliant)

1.12MP/8MP(4K)/6MP/5MP/4MP/2MP H.265 PoE IP Camera 2.Fixed Lens/ Motorized Lens Optional 3.Support 2DNR/ 3DNR/ Sense-up/ WDR Functions etc.

4.Built-in Mic./Speaker or Audio in/out Optional(RCA Cable Interface) 5.Support RTSP&Onvif(17.2 with profile S),Compatible with HIK/DH/UNV/TVT NVRS 6.SDK/CGI Available

IPC IR Night Vision Camera Series

Professional OEM/ODM CCTV Camera Manufacturer.



- BC-IE232RW-2MS(2MP@30fps)
- BC-IE232RW-5MS(5MP@25fps)
- BC-IE232RW-6M6(6MP@25fps)
- BC-IE232RW-8MS(8MP@20fps)
- BC-IE232RW-8MH(8MP@30fps)
- 6pcs LEDs 20m IR Distance
- 2.8mm Fixed Lens
- IP66,PoE&DC12V



- BC-IE332RW-2MS(2MP@30fps)
- BC-IE332RW-5MS(5MP@25fps)
- BC-IE332RW-6MH(6MP@25fps)
- BC-IE332RW-8MS(8MP@20fps)
- BC-IE332RW-8MH(8MP@30fps)
- BC-IE332RW-9MS(12MP@25fps)
- 6pcs LEDs 25m IR Distance
- 2.8mm Fixed Lens
- IP66,PoE&DC12V



- BC-IV232RW-2MS(2MP@30fps)
- BC-IV232RW-5MS(5MP@25fps)
- BC-IV232RW-6M6(6MP@25fps)
- BC-IV232RW-8MS(8MP@20fps)
- BC-IV232RW-8MH(8MP@30fps)
- 18pcs LEDs 25m IR Distance
- 2.8mm Fixed Lens
- IP66,PoE&DC12V



- BC-IV30BRW-2MS(2MP@30fps)
- BC-IV30BRW-5MS(5MP@25fps)
- BC-IV30BRW-6M6(6MP@25fps)
- BC-IV30BRW-8MS(8MP@20fps)
- BC-IV30BRW-8MH(8MP@30fps)
- BC-IV30BRW-9MS(12MP@25fps)
- 4pcs LEDs 35m IR Distance
- 5X 2.7-13.5mm Motor Lens
- IP66,PoE&DC12V



- BC-IB612RW-2MS(2MP@30fps)
- BC-IB612RW-5MS(5MP@25fps)
- BC-IB612RW-6M6(6MP@25fps)
- BC-IB612RW-8MS(8MP@20fps)
- BC-IB612RW-8MH(8MP@30fps)
- 16pcs LEDs 15m IR Distance
- 2.8mm Fixed Lens
- IP66,PoE&DC12V



- BC-IB71BRW-2MS(2MP@30fps)
- BC-IB71BRW-5MS(5MP@25fps)
- BC-IB71BRW-6M6(6MP@25fps)
- BC-IB71BRW-8MS(8MP@20fps)
- BC-IB71BRW-8MH(8MP@30fps)
- 6pcs LEDs 35m IR Distance
- 5X 2.7-13.5mm Motor Lens
- IP66,PoE&DC12V



SD Card



Waterproof



Junction box



Bracket

Features

1.12MP/8MP(4K)/6MP/5MP/4MP/2MP H.265 PoE IP Camera
2.Fixed Lens/ Motorized Lens Optional
3.Support 2DNR/ 3DNR/ Sense-up/ WDR Functions etc.
4.Built-in Mic,Audio in/out Optional(RCA Cable Interface)
5.Support RTSP&Onvif(17.2 with profile S),Compatible with HIK/DH/UNV/TVT NVRS
6.SDK/CGI Available

(NDAA Compliant)

IPC 180 Degree Super Wide Angle Series

Professional OEM/ODM CCTV Camera Manufacturer.



. BC-IB814DW-4M2(4MP@20fps)
. BC-IB812DW-8M2(8MP@20fps)
. 8MP(Max. 4096*1944)
. Smart Dual Light Colorvu
. Two Way Audio/SD Card
. viewing angle of 180°
. 4mm/2.8mm Fixed Lens*2
. Max.256G SD Card
. IR range: (IR: 20m) + (White Light :15m)
. IP66,PoE&DC12V



. BC-IE514DW-4M2(4MP@20fps)
. BC-IE512DW-8M2(8MP@20fps)
. 8MP(Max. 4096*1944)
. Smart Dual Light Colorvu
. Two Way Audio/SD Card
. viewing angle of 180°
. 4mm/2.8mm Fixed Lens*2
. Max.256G SD Card
. IR range: (IR: 20m) + (White Light :15m)
. IP66,PoE&DC12V



. BC-IB68GWW-5MS(5MP@25fps)
. 5MP(Max. 2592*1944)
. Smart Dual Light Colorvu
. Two Way Audio/SD Card
. Viewing angle of 180°
. 2.1mm Fixed Lens
. Max.256G SD Card
. IR range: (IR: 20m) + (White Light :15m)
. IP66,PoE&DC12V



. BC-IV20GWW-5MS(5MP@25fps)
. 5MP(Max. 2592*1944)
. Smart Dual Light Colorvu
. Two Way Audio/SD Card
. Viewing angle of 180°
. 2.1mm Fixed Lens
. Max.256G SD Card
. IR range: (IR: 20m) + (White Light :15m)
. IP66,PoE&DC12V

Features

1.8MP/4MP H.265 PoE IP Camera
2.Support 2DNR/ 3DNR/ Sense-up/ WDR Functions etc.
3.Support RTSP&Onvif(17.2 with profile S)&HIK Protocol
Compatible with HIK/DH/UNV/TVT NVRS
4.SDK/CGI Available



(Left lens imaging effect) (Right lens imaging effect)



(Binocular splicing ultra-wide angle camera imaging effect: no distortion, high fidelity.)

(NDAA Compliant)

IPC LPR IP Camera Series

Professional OEM/ODM CCTV Camera Manufacturer.

Camera1





Braket(Optional)

- BC-IB996FW-2MS(2MP@30fps)
- BC-IB996FW-5MH(5MP@30fps)
- 10X Zoom (5-50mm Manual Lens)
- BLC/3D DNR/WDR
- 4pcs White Light LEDs 35m
- IP66,PoE,DC12V

Camera2



- BC-IB73BWW-4M4(4MP@25fps)
- High quality imaging with 4 MP resolution
- Excellent low-light performance with powered-by-DarkFighter technology
- Efficient H.265+ compression technology
- Clear imaging against strong back light due to 120 dB true WDR technology



Normal Camera
VS
License Plate Camera



Features

Camera1: • Support RTSP&Onvif(17.2 with profile S) Compatible with many third-party NVRs and CMS

• Support multiply Web Browsers: IE/Firefox/Chrome/Safari etc.

Camera2: • All-day vehicle capture rate is higher than 99.9%;

• All-day license plate recognition rate is higher than 95%;

• Support cloud control function for parameter configuration, video preview and remote upgrade;

• SDK Available

(NDAA Compliant)

IPC Mini Hidden&Fisheye Camera Series

Professional OEM/ODM CCTV Camera Manufacturer.



- BC-IM1170B-2MS(2MP@30fps)
- BC-IM1170B-5M4(5MP@25fps)
- BC-IM1170B-6M6(6MP@25fps)
- BC-IM1170W-8MS(8MP@20fps)
- 3.7mm Pinhole Lens
- Built-in Mic(Optional)
- PoE&DC12V



- BC-IM1120B-2MS(2MP@30fps)
- BC-IM1120B-5M4(5MP@25fps)
- BC-IM1120B-6M6(6MP@25fps)
- BC-IM1120W-8MS(8MP@20fps)
- 2.8mm Fixed Lens
- Built-in Mic(Optional)
- PoE&DC12V



- BC-IM2170W-2MS(2MP@30fps)
- BC-IM2170W-5M4(5MP@25fps)
- BC-IM2170W-6M6(6MP@25fps)
- 3.7mm Pinhole Lens
- Built-in Mic(Optional)
- BLC/3D DNR/WDR
- Plug&Play onvif compatibity
- PoE&DC12V



- BC-IM217RW-2MS(2MP@30fps)
- BC-IM217RW-5M4(5MP@25fps)
- BC-IM217RW-6M6(6MP@25fps)
- BC-IM217RW-8ME(8MP@20fps)
- 3.7mm Pinhole Lens
- 48pcs 940nm Invisible IR Leds 15m
- Built-in Mic(Optional)
- PoE&DC12V



- BC-IM3170W-2MS(2MP@30fps)
- BC-IM3170W-5M4(5MP@25fps)
- BC-IM3170W-6M6(6MP@25fps)
- BC-IM3170W-8ME(8MP@20fps)
- 3.7mm Pinhole Lens
- PoE&DC12V



- BC-IF131RW-2MS(2MP@30fps)
- BC-IF131RW-5MS(5MP@25fps)
- BC-IF131RW-8MS(8MP@20fps)
- BC-IF131RW-8MH(8MP@30fps)
- BC-IF131RW-9MS(12MP@25fps)
- 1.7/1.44mm Fisheye Lens
- Two-way Audio(Optional)
- 3pcs Array IR Leds 15m IR
- IP66,PoE&DC12V



Power over Ethernet | Audio | SD Card | Hidden

Features

1.12MP/8MP(4K)/6MP/5MP/4MP/2MP H.265 PoE IP Camera
2.Support 2DNR/ 3DNR/ Sense-up/ WDR Functions etc.
3.Built-in Mic./Speaker or Audio in/out Optional(RCA Cable Interface)
4.Support RTSP&Onvif(17.2 with profile S),Compatible with HIK/DH/UNV/TVT NVRS
5.SDK/CGI Available

(NDAA Compliant)

HD Analog Camera Series

Professional OEM/ODM CCTV Camera Manufacturer.



- BC-TV203RW-2F3(2MP@30fps)
- BC-TV203RW-5FK(5MP@20fps)
- BC-TV203RW-8FS(8MP@15fps)
- TVI / CVI / AHD / CVBS 4 in 1 Solution
- 15pcs IR LEDs 15m IR
- 3.6mm Fixed Lens
- IP66,DC12V



- BC-TP30BRW-2FS(2MP@30fps)
- BC-TP30XRW-2FS(2MP@30fps)
- TVI / CVI / AHD / CVBS 4 in 1 Solution
- 2PCS LEDS 35m IR
- 5X 2.7-13.5mm AF Motor Len
  12X 5-60mm AF Motor Lens
- Pan:0~360° /Tilt:0~90°
- IP66,DC12V



- BC-TB683WW-2F3(2MP@30fps)
- BC-TB683WW-2FC(5MP@20fps)
- BC-TB683WW-8FH(8MP@15fps)
- TVI / CVI / AHD / CVBS 4 in 1 Solution
- 6pcs IR Leds 30m IR
- 3.6mm Fixed Lens
- IP66,DC12V



- BC-TF131RW-5FK(5MP@20fps)
- TVI / CVI / AHD / CVBS 4 in 1 Solution
- 3pcs IR Leds 15m IR
- 1.44mm Fisheye Lens
- IP66,DC12V



- BC-TE213RW-2F3(2MP@30fps)
- BC-TE213RW-5FK(5MP@20fps)
- BC-TE213RW-8FH(8MP@15fps)
- TVI / CVI / AHD / CVBS 4 in 1 Solution
- 18pcs IR LED 15m IR
- 3.6mm Fixed Lens
- IP66,DC12V



- BC-TE318RW-2F3(2MP@30fps)
- BC-TE318RW-5FK(5MP@20fps)
- BC-TE318RW-8FS(8MP@15fps)
- TVI / CVI / AHD / CVBS 4 in 1 Solution
- 24pcs IR LED 30m IR
- 5X 2.7-13.5mm Manual Varifocal Lens
- IP66,DC12V



- BC-TE253WW-2F3(2MP@30fps)
- BC-TE253WW-5FK(5MP@20fps)
- BC-TE253WW-8FS(8MP@15fps)
- BC-TE253WW-8F8(8MP@15fps)
- TVI / CVI / AHD / CVBS 4 in 1 Solution
- 2pcs Warm Light LEDs15m
- 3.6mm Fixed Lens
- IP66,DC12V



- BC-TE2A3WW-2F3(2MP@30fps)
- BC-TE2A3WW-5FK(5MP@20fps)
- BC-TE2A3WW-8FS(8MP@15fps)
- BC-TE2A3WW-8F8(8MP@15fps)
- TVI / CVI / AHD / CVBS 4 in 1 Solution
- 2pcs Warm Light LEDs15m
- 3.6mm Fixed Lens
- IP66,DC12V

Features

1. 1.8MP/5MP/2MP 4in1 TVI/AHD/CVI/Analog
2. Fixed Lens/ Manual Varifocal Lens/ Motorized Lens Optional
3. Support 2DNR/ 3DNR/ Sense-up/ D-WDR Functions etc.
4. Support UTC Control Function (RS-485 Control function Optional)
5. Support Coaxial Audio(TVI & CVI)

(NDAA Compliant)

Smart Home Series(Wifi Camera)

Professional OEM/ODM CCTV Camera Manufacturer.



- BC-WB683RW-2T2(2MP@20fps)
- BC-WB683RW-4T4(4MP@20fps)
- BC-WB683RW-5T5(5MP@20fps)
- BC-WB683SW-8TS(8MP@10fps)
- 3.6mm fixed lens
- Built-in Mic and Speaker
- 30m IR
- H.264/H.265 Video Compression
- Support SD Card, Maxp to 256G
- Waterproof IP66



- BC-WP203RW-2T2(2MP@20fps)
- BC-WP203RW-4T4(4MP@20fps)
- BC-WP20BRW-5TS(5MP@20fps)
- 3.6mm/2.7~13.5mm 5X Optical Lens
- Built-in Mic and Speaker
- 30m IR
- H.264/H.265 Video Compression
- Support SD Card, Maxp to 256G
- Waterproof IP66



- BC-WP32BRW-2T2(2MP@20fps)
- BC-WP32BRW-5T5(5MP@20fps)
- 35m IR+25m white light
- 2.7~13.5mm 5X Optical Lens
- Support humanoid tracking
- Wall mounting and hoisting
- 35m IR+25m white light
- H.264/H.265 Video Compression
- Support WiFi, up to 100m
- Waterproof IP66



- BC-WP293RW-2T2(2MP@20fps)
- BC-WP293RW-4T4(4MP@25fps)
- Support humanoid tracking
- 5~20X Optical Lens
- Supports voice alerting
- Support SD Card, Maxp to 256G
- Support 4G/WiFi, up to 100m
- 50m IR+30m white light
- Supports two-way Audio
- Waterproof IP66




- BC-WP223DW-2T2(2MP@20fps)
- BC-WP223DW-4T4(4MP@25fps)
- BC-WP22BDW-2T2(5MP@20fps)
- 40m IR+30m white light
- 3.6mm/2.7~13.5mm 5X Optical Lens
- Support preset point and cruise
- Supports two-way Audio
- Support humanoid tracking
- Support wall mounting and hoisting
- Support 4G/WiFi, up to 100m
- Waterproof IP66



- BC-WP353DW-2T2(2MP@20fps)
- BC-WP353DW-5T5(5MP@20fps)
- BC-WP35BDW-5T5(5MP@20fps)
- 40m IR+30m white light
- 3.6mm/2.7~13.5mm 5X Optical Lens
- Support humanoid tracking
- Wall mounting and hoisting
- Red& Blue sound and light alarm
- Support 4G/WiFi, up to 100m
- Waterproof IP66



- BC-WP58YDW-2T2(5MP@20fps)
- BC-WP58YDW-5T5(5MP@20fps)
- 100m IR+40m white light
- Super laser night vision
- Support preset point and cruise
- Supports two-way Audio
- Support intelligent humanoid tracking
- Support 4G/WiFi, up to 100m
- Support SD Card, Max. up to 256G
- 20X Optical zoom



Features

1. ONVIF P2P H.265/H.264 IP Camera
2. Recording: Motion Detection, Schedule
3. Support Motion Detection and Alarm Notification
4. Multiple Ways of Configuration: LAN/AP (Access Point)/Scan/UID Adding
5. Support WiFi SD Card(Max 256G) Built in MIC and Speaker

Professional OEM/ODM CCTV Camera Manufacturer.

AOV Series

AOV (Always On Video) camera is an intelligent monitoring device with low power consumption technology, which has significant advantages in power consumption control, video continuity, environmental adaptability, etc., and is suitable for outdoor, remote areas and temporary monitoring scenarios.

1. Support 7x24 hours of uninterrupted recording, and can continue to record when no one triggers

2. Ultra-low power consumption, long-lasting battery life, with solar power supply, it can operate for a long time in a non-power environment

3. Intelligent AI, support humanoid detection, license plate recognition and other functions, when triggered, it can quickly switch from low-power mode to full-frame rate recording mode.

4. Waterproof and dustproof, can work stably under extreme conditions such as rain, snow, high temperature, etc5. Support 4G/WIFI dual networking mode, easy to install



· BC-SP223DW-2T2
· BC-SP22BDW-2T2
· BC-SP22BDW-5T5
· 12W SOLAR-POWERED WITH BUILT-IN BATTERY (15600MA)
· Support 4G/WiFi, up to 100m
Human detection (unmanned single-frame recording, manned full-frame recording)
· Support human tracking
· Support PTZ, horizontal 350° rotation, vertical 0°~90° .
Horizontal speed 0.1°~35°/s, vertical speed 0.1°~20°/s.3.6mm/2.7~13.5mm 5X optical lens
· Support intelligent dual-light, full-color night vision

Low-power solar Series

1. Solar power, Extremely low power consumption(Consumes about 250mAh of standby current per day)

2. PIR(human motion detection), when someone is close to the camera within 10meters, within 1 second to start the camera to shoot video, and can pushwarning messages to APP mobile phone

3. Support mobile remote wake-up device

4. Support 4G/WIFI (4G SIM cards required)

5. Night camera can manually switch white light and infrared light mode

6. Induction street light, someone approaching 10 meters, the street light will be on, and start the camera (need to adjust to white light mode)7. native storage (need to insert TF card)



. BC-SLB-4020
. BC-SLB-4040
. BC-SLB-6020
. 20W SOLAR POWERED WITH BUILT-IN BATTERY (16000MA)
. Support two-way voice intercom, SD card (up to 256G)
. Support 4G/WiFi, up to 100m
. Support PIR body sensing, humanoid tracking
. Support PTZ, 350° rotation horizontally, 0°~90° vertically
. 3.6mm/2.7~13.5mm 5X optical lens optional
. Support intelligent dual-light, full-color night vision



. BC-SLB-4020
. BC-SLB-4040
. BC-SLB-6020
. 20W SOLAR POWERED WITH BUILT-IN BATTERY (20800MA)
. Support two-way voice intercom, SD card (up to 256G)
. Support 4G/WiFi, up to 100m
. Support PIR body sensing, humanoid tracking
. Support PTZ, 350° rotation horizontally, 0°~90° vertically
. Support dual lens, bullet 3.6mm, dome 3.6mm/5X optical zoom optional
. Support intelligent dual-light, full-color night vision

(NDAA Compliant)

USB Camera Series

Professional OEM/ODM CCTV Camera Manufacturer.



· BC-U20M37-2S1(2MP@30FPS)
· BC-U20M46-4S2(2K@30FPS)
·BC-U20M78-8S3(4K@30FPS)
· High sensitivity sensor
· Support built-in full directional polarized microphone and dual microphone;
· Support digital noise reduction function, 2-DNR/3-DNR;
· Support video format：YUV, MJPG, H.264
· Support 2.8mm/3.6mm fix lens.
· Support privacy cover.
· Supports UVC1.1/1.5 protocol, drive free.
· USB 2.0 Type-A interface



· BC-U30M37-2S1(2MP@30FPS)
· BC-U30M46-4S2(2K@30FPS)
· BC-U30M78-8S3(4K@30FPS)
· High sensitivity sensor
· Support built-in full directional polarized microphone and dual microphone;
· Support digital noise reduction function, 2-DNR/3-DNR;
· Support video format：YUV, MJPG, H.264
· Support 3.6mm fix lens/Autofocus lens
· Support privacy cover.
· Supports UVC1.1/1.5 protocol, drive free.
· USB 2.0 Type-A interface



· OEM/ODM customized modules/finished products
· Support professional high performance CMOS Image sensor with resolution up to 12MP
· Support USB1.1/2.0/3.0 (Type-A/Type-C) interface.
· Support UVC1.1/1.5 protocol.
· Supports 2MP/2K/4K resolution.
· Support maximum frame rate up to 120fps
· Support 120dB dual frame synthesized WDR
· Support window hello
· Support fixed-focus distortion-free lens, auto-focus lens.
· Support dual-mic pickup



· BC-U12M37-2S1(2MP@30FPS)
· BC-U12M46-4S2(2K@30FPS)
· BC-U12M78-8S3(4K@30FPS)
· High sensitivity sensor
· Support built-in full directional polarized microphone and dual microphone;
· Support digital noise reduction function, 2-DNR/3-DNR;
· Support video format：YUV, MJPG, H.264
· Support 2.8mm/3.6mm fix lens.
· Support privacy cover.
· Support white LED fill light.
· Supports UVC1.1/1.5 protocol, drive free.
· USB 2.0 Type-A/Type-C interface



· BC-U15M37-2S1(2MP@30FPS)
· BC-U15M46-4S2(2K@30FPS)
· BC-U15M78-8S3(4K@30FPS)
· High sensitivity sensor
· Support built-in full directional polarized microphone and dual microphone;
· Support digital noise reduction function, 2-DNR/3-DNR;
· Support video format：YUV, MJPG, H.264
· Support 3.6mm fix lens/Autofocus lens
· Support privacy cover.
· Supports UVC1.1/1.5 protocol, drive free.
· USB 2.0 Type-A/Type-C interface

Features

1. Support WINDOWS HELLO
2. Support USB1.1/USB2.0/USB3.0 (type-A, B or C) interface, plug and play;
3. Support YUV2/MJPG/H.264 video output.
4. Support Windows XP SP2 or later, Linux kernel 2.6 or higher.
5. Support Full HD video recording (up to 12MP (4000x300) pixels);
6. Built-in omnidirectional electret microphone and dual microphone
7. Support dual cameras,face recognition.

(NDAA Compliant)

AI Camera Systems

Professional OEM/ODM CCTV Camera Manufacturer.





- BC-NK04E255D-RP4
- 4ch POE NVR with AI function
- 8MP*10ch Input(4xPOE+6xLAN)
- 1ch ext audio inpout/output
- Support 1*14TB HDD, HDMI/VGA output
- 5MP30fps 3.6mm fixed Lens Camera
- Smart Dual Light(20m IR+15m Flood Light)
- Support 4ch face capture and comparison
- Support Electronic fence/cross line/statistics



- BC-NK08E255D-RP8
- 8ch POE NVR with AI function
- 8MP*10ch Input(8xPOE+2xLAN)
- 1ch ext audio inpout/output
- Support 1*14TB HDD, HDMI/VGA output
- 5MP30fps 3.6mm fixed Lens Camera
- Smart Dual Light(20m IR+15m Flood Light)
- Support 8ch face capture and comparison
- Support Electronic fence/cross line/statistics
- Bllut-in Mic/POE

Features

1. 1/2.7" high-sensitivity CMOS sensor(up to 5MP)
2. Support inclusive AI functions such as electronic fence, cross-line, off-duty, and passenger flow statistics.
3. Multi-level alarm linkage mode, which can be associated with video, lighting, APP push and external GPIO, etc.
4. A variety of ways to alarm storage video mode, a variety of convenient search mode, including map search.
5. Support SDK/API, (Secondary development functions is available).



- BC-NK12B685D-RP12
- 12ch POE NVR with AI function
- 8MP*16ch Input(12xPOE+4xLAN)
- 1x8MP or 8xD1(sub stream) playback
- Support 1*14TB HDD, HDMI/VGA output
- 5MP30fps 3.6mm fixed Lens Camera
- Smart Dual Light(20m IR+15m Flood Light)
- Support 12ch face capture and comparison
- Support Electronic fence/cross line/statistics
- Bllut-in Mic/POE




- BC-NK16B685D-RP16
- 16ch POE NVR with AI function
- 8MP*20ch Input(16xPOE+4xLAN)
- 1ch ext audio inpout/output
- Support 2*14TB HDD, HDMI/VGA output
- 5MP30fps 3.6mm fixed Lens Camera
- Smart Dual Light(20m IR+15m Flood Light)
- Support 16ch face capture and comparison
- Support Electronic fence/cross line/statistics
- Bllut-in Mic/POE

IPC USB HDMI Camera PCBA Customized Service


Professional OEM/ODM CCTV Camera Manufacturer.

OEM/ODM product

- Provide SDK/API interface, support 2 times development.
- High-quality sensor, up to 1/1.2" size, up to 12MP (4000x3000) resolution
- The maximum frame rate is 120fps. Maximum dynamic range 130dB (three-frame compositing).
- Powerful AI computing power, up to 6Tbit/s..
- Support custom CS lens, 5X/10X/20X/30X AF lens. Support for IRIS.
- AI-ISP, image enhancement, lower noise, higher image quality.
- Support network protocols such as CGI, HTTPS, GB28181, SIP, RTMP, RTP, FTP, RTCP, RTSP, NTP, DHCP, DNS, SSL/TLS, WebSocket, and standard protocols such as ONVIFSupport
  HDMI (4K30)/USB(4K30)/SDI(FHD@60)/CVBS format output.
- Optional enclosure - bullet, dome machine riot conch.




- **3516AV100+1/1.8"Sony385**
- 2MP@30fps（1920x1080）main stream，D1@30fps sub stream
- Frame rate enhancement：2MP@120fps
- Highest bitrate：upto 32Mbps
- support moto lens with auto focus



- **3516DV500+1/1.8"Sony568**
- 8Gbit DDR/1Gbit Nor flash
- 5MP@30fps(2448x2048) main stream,
  D1@30fps sub stream,D1@30fps thr stream
- Frame rate enhancement,2MP@60fps
- Highest bitrate：upto 32Mbps
- support moto lens with auto focus



- **3516DV500+1/1.8"Sony385**
- 1GB DDR，16GB eMMC
- 2MP@30fps(1920x1080)main stream,
  D1@30fps sub stream,D1@30fps thr stream
- Highest bitrate,upto 32Mbps
- Support moto lens with auto focus
- OPTIONAL：LPR（AS）



- **SS928V100+1/1.2"Sony585**
- 8GB DDR，16GB EMMC
- 8MP@30fps□3840x2160□main stream□
  D1@30fps sub stream
- Highest bitrate□upto 16Mbps
- Frame rate enhancement：8MP@60fps
- support moto lens with auto focus

A Series NVR

Professional OEM/ODM CCTV Camera Manufacturer.




Supports a full range of
Ip Cameras



AI This Mstar NVR also supports AI Features from Mstar AI IP Cameras. The AI features available depend on the camera model being used. There are No built-in AI Features on this NVR

Features

1.H.265/H.264 High Profile Dual Stream Video CompressionHDMI/VGA Output
2.Multi-mode Recording: Manual/ Schedule/ Motion / Alarm
3.Support 8/12/20/36CH Playback
4.Support TCP/IP, HTTP, DHCP,DNS,DDNS,RTP /RTCP/RTSP/NTP, FTP,ONVIF Network Protocol
5.Remote Control via Web or CMS: Preview, Playback, Backup, PTZ and Configuration
6.Multi-user Online Simultaneously
7.Support ONVIF Profile T/S
8.Powerful Smartphone App (iPhone, Andriod with P2P function)



. BC-N121-9MD1-P4(4POE+4LAN)
. BC-N201-9MD1-P8(8POE+8LAN)
. BC-N362-9MD1-P16(16POE+16LAN)
. Capability：1x12MP@30fps,8xD1@30
. format：H.265/H.264
. bandwidth:80/280Mbps
. video：1CH HDMI,(12MP@30fps) 1CH VGA（FHD) 1xRJ45（100M）,8xRJ45（100M/1000M，POE)
. P2P:VideoLink



. BC-N121-9MD1(12CH)
. BC-N201-9MD1(20CH)
. BC-N362-9MD1(36CH)
. Capability：1x12MP@30fps,8xD1@30
. Bandwidth：64/80/280Mbps
. Format：H.265/H.264
. video：1CH HDMI,(12MP@30) 1CH VGA(FHD)
. Network：1 x RJ 45（100/1000M)
. P2P ：VideoLink

12MP
up to 12M P .Cameras Resolution

H.265
Professional Video Compression

PoE
Power over Ethernet

P2P
Free APP and PC Client for Remote Access

24/7
Support maximum of 12TB for a single disk

(NDAA Compliant)

(NDAA Compliant)

Professional OEM/ODM CCTV Camera Manufacturer.

plug-and-play



Features

1.H.265/H.264 High Profile Dual Stream Video Compression
HDMI/VGA Output
2.Multi-mode Recording: Manual/ Schedule/ Motion/ Alarm
3.Support 8/16/32 CH Playback
4.Support TCP/IP, HTTP, DHCP,DNS,DDNS,RTP/RTCP/RTSP/NTP, FTP, ONVIF Network Protocol
5.Remote Control via Web or CMS: Preview, Playback, Backup, PTZ and Configuration
6.Multi-user Online Simultaneously
7.Support ONVIF Profile T/S
8.Powerful Smartphone App (iPhone, Andriod with P2P function)

POE NVR



- BC-NVR3116LS-P8（8CH PoE+8CH LAN）
- BC-N162UN-3BIQ-P16（16CH PoE）
  1/2 x HDD（up to 10T）
  Capability：BC-NVR3116LS-P8:1x4K@30fps,16xD1@30fps
  BC-N162UN-3BIQ-P16:2x12MP@30fps,16x720P@30fps
- Format:Ultra265/H.265/H.264
- Bandwidth:64Mbps/160Mbps
- Video:1CH HDMI,(4K@30) 1CH VGA(FHD)
- P2P:Guard Viewer

NO POE NVR



- BC-NVR3232S1(4K 32CH)
- BC-NVR5864B(4K 64CH)
- Capability：1x4K@30fps,32xD1@30fps
- 32CH,2 x HDD（up to 10T），
- 64CH, 8x HDD（up to 12T）
- Format:Ultra265/H.265/H.264
- Bandwidth:160Mbps/256Mbps
- Video:1CH HDMI,(4K@30) 1CH VGA（FHD）
- P2P:Guard Viewer



CCTV NVR System Series

Professional OEM/ODM CCTV Camera Manufacturer.



- BC-NK08B688D-AP8
- （8ch PoE+8ch LAN) 16CH H.265 12MP NVR 16ch Playback
- RCA audio 1ch in+ 1ch out +HDMI audio out
- Support 1*12TB HDD, HDMI/VGA output
- 8MP 2. 8mm Lens Smart Dual Light(20m IR+ 15m Flood Light), Mic. POE Bullet Camera
- APP:Videolink



- BC-NK16E258D-AP16
- （16ch PoE+16ch LAN) 32CH H.265 12MP NVR 32ch Playback
- RCA audio 1ch in+ 1ch out +HDMI audio out
- Support 2*12TB HDD, HDMI/VGA output
- 8MP 2.8mm Lens Smart Dual Light(20m IR+ 15m Flood Light), Mic. POE Dome Camera
- APP:Videolink



- BC-NK08E258DU8
- 8+8ch H.265 4K POE NVR, 8ch Playback
- 1ch RCA audio output/HDMI Audio output
- Support 1*10TB HDD, HDMI/VGA output
- 1/2.7"CMOS sensor, 8MP Resolution, 8MP 2.8mm Lens Smart Dual Light(20m IR+ 15m Flood Light), Mic. POE Dome Camera
- APP:Guard View



- BC-NK16B688DU16
- 16ch H.265 4K POE NVR, 16ch Playback
- 1ch RCA audio output/HDMI Audio output
- Support 2*10TB HDD, HDMI/VGA output
- 1/2.7"CMOS sensor, 8MP Resolution, 8MP 2.8mm Lens Smart Dual Light(20m IR+ 15m Flood Light), Mic. POE Bullet Camera
- APP:Guard View



- BC-NK04B404D-AM8
- （8ch PoE+8ch LAN) 16CH H.265 12MP NVR built-in 12.1" monitor, 8ch Playback
- Capability：1x4K@30fps,16xD1@30fps
- RCA audio 1ch in+ 1ch out +HDMI audio out
- Support 1*12TB HDD, HDMI/VGA output
- 4MP 2. 8mm Lens Smart Dual Light(20m IR+ 15m Flood Light), Mic. POE Bullet Camera
- APP:Videolink



- BC-NK08B404D-AM8
- （8ch PoE+8ch LAN) 16CH H.265 12MP NVR built-in 12.1" monitor, 8ch Playback
- Capability：1x4K@30fps,16xD1@30fps
- RCA audio 1ch in+ 1ch out +HDMI audio out
- Support 1*12TB HDD, HDMI/VGA output
- 4MP 2. 8mm Lens Smart Dual Light(20m IR+ 15m Flood Light), Mic. POE Bullet Camera
- APP:Videolink

Features

1. H.265/H.264 High Profile Dual Stream Video Compression HDMI/VGA Output
2. Multi-mode Recording: Manual/ Schedule/ Motion/ Alarm
3. Support 8/16/32 CH Playback
4. Support TCP/IP, HTTP, DHCP,DNS,DDNS,RTP/RTCP/RTSP/NTP, FTP, ONVIF Network Protocol
5. Remote Control via Web or CMS: Preview, Playback, Backup, PTZ and Configuration
6. Multi-user Online Simultaneously
7. Support ONVIF Profile T/S
8. Powerful Smartphone App (iPhone, Andriod with P2P function)

DVR Series

Professional OEM/ODM CCTV Camera Manufacturer.



Features

1.Support input up to 8MP@15fps,Support 8MP@6fps recording,
2.Support 4in1 input, automatic identification.
3.Support UTC protocol, support Rs485.
4.Supports full-channel coaxial audio. (TVI audio supported)
5.Support a variety of fill light modes, including white light, infrared, mobile trigger white light dual light, etc.
6.Support a variety of AI functions such as human shape detection and cross-line detection.
7.Support face capture function.
8.Support the interchange of analog channels and digital channels, and (onvif protocol) can be connected to IPC.

T Series



- BC-D041T3-2NF1S(4CH/1*HDD)
- BC-D081T5-8PM1(8CH/1*HDD)
- BC-D162T5-8NM2(16CH/2*HDD)
- BC-D322T5-5NM1L(32CH/2*HDD)
- Support 4/8/16/32 CH Playback
- Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access
- Video Ability: 1080N/5MN/5MP/8MN/8MP optional
- Support audio 1*input/1*output
- Support HDMI/VGA/TV output
- APP:TSeye

U Series



- BC-D041U-5NG3(4CH/1*HDD@8T)
- BC-D081U-8NQ3(8CH/1*HDD@8T)
- BC-D162U-8NQ3(16CH/2*HDD@8T)
- Support 4/8/16 CH Playback
- Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access
- Video Ability: 5MN/5MP/8MN/8MP optional
- Support audio 1*input/1*output
- HDMI and VGA simultaneous output
- Support mainstream cameras of ONVIF and RTSP protocols
- P2P:Guard Viewer

CCTV DVR System Series

Professional OEM/ODM CCTV Camera Manufacturer.

T Series



- BC-DK04E335NDA-T37
- 4ch H.265 5MP recording
- 4ch Playback
- HD video image, Plug and Play
- 4ch audio input/1ch audio output
- HDMI(4K)/VGA
- Support 1*8TB HDD
- 1/2.5" 5MP CMOS sensor, 2.8mm Lens, 5MP TVI/5MP AHD/4MP CVI Camera
- APP : Tseye

T Series



- BC-DK04E2A5NDA-T37
- 8ch H.265 5MP recording
- 8ch Playback
- HD video image, Plug and Play
- 8ch audio input/1ch audio output
- HDMI(4K)/VGA
- Support dual light
- Support 1*8TB HDD
- 1/2.5" 5MP CMOS sensor, 2. 8mm Lens, 5MP TVI/5MP AHD/4MP CVI Camera
- APP : Tseye

U Series



- BC-DK08E2A5NDA-UG3
- 8ch channel BNC input/5MP recording
- Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access
- Support audio over coaxial cable(only for TVI cameras)HDMI and VGA simultaneous output
- Support dual light
- Support 1*8TB HDD
- 1/2.5" 5MP CMOS sensor, 2.8mm Lens, 5MP TVI/5MP AHD/4MP CVI Camera
- APP:Guard Viewer

T Series



- BC-DK04E255NDA-T37
- 16ch H.265 5MP recording
- 16ch Playback
- HD video image, Plug and Play
- 8ch audio input/1ch audio output
- HDMI(4K)/VGA
- Support dual light
- Support 2*8TB HDD
- 1/2.5" 5MP CMOS sensor, 2. 8mm Lens, 5MP TVI/5MP AHD/4MP CVI Camera
- APP : Tseye

T Series



- BC-DK08E255NRA-TM5
- 8CH 5MP with 10.1 inch display XVR
- Support TVI/AHD/CVI/CVBS/IPC 5-in-1 8*5MN@12.5fps input(8*BNC)
- Support 1*6TB HDD, HDMI/VGA output 8*5MP@12fps 3.6mm fixed Lens Camera
- Support for coaxial audio
- Support 1 audio output (XVR)
- APP : Tseye

Features

1. Support input up to 8MP@15fps,Support 8MP@6fps recording,
2. Support 4in1 input, automatic identification.
3. Support UTC protocol, support Rs485.
4. Supports full-channel coaxial audio. (TVI audio supported)
5. Support a variety of fill light modes, including white light, infrared, mobile trigger white light dual light, etc.
6. Support a variety of AI functions such as human shape detection and cross-line detection.
7. Support face capture function.
8. Support the interchange of analog channels and digital channels, and (onvif protocol) can be connected to IPC.

Junction Box and Bracket

(Support Hik DH Camera and Besview Camera)

BC-JBE21W	BC-JBE31W	BC-JBE33W	BC-JBV20W	BC-JBE20W	BC-JBE30W	BC-JBE40W	DH-PFA130-E	DH-PFB203W	BC-WBE31W
Besview camera	Besview camera	Besview camera	Besview camera	Hik camera	Hik camera	Hik camera	DH camera	DH camera	Besview camera
		 Hik camera 	 Hik camera 						